



PRODUCT IDENTIFICATION



Brand	CARCAMP
Carcamp product	AURORA 3
Product family	AURORA
Segment	Economy soft-shell rooftop tent
Carcamp internal code	000163400000
EAN	8003168059431

LOGISTICS AND SHIPPING DATA

Gross weight	66,40 kg / 146.39 lb
Package dimensions (W x D x H)	173 x 134 x 36 cm / 68.11 x 52.76 x 14.17 in
Total packaging weight	17,613 kg / 38.83 lb
Cardboard	10 kg / 22.05 lb
MDF	5,60 kg / 12.35 lb
Polyethylene / polypropylene	1,70 kg / 3.75 lb (polyethylene)
Bubble wrap / film	0,313 kg / 0.69 lb

INSTALLATION AND FOOTPRINT DATA

Tent weight mounted on vehicle	47,50 kg / 104.72 lb
Footprint, tent closed and mounted (W x D x H)	166 x 125 x 36 cm / 65.35 x 49.21 x 14.17 in (external dimension with ladder mounted, including natural protrusions)
Closed tent profile footprint (W x D x H)	163 x 120,50 x 35 cm / 64.17 x 47.44 x 13.78 in (technical dimension)
Open tent profile footprint (W x D x H)	166 x 241 x 110 cm / 65.35 x 94.88 x 43.31 in
Lower mounting system layout	17 cm / 6.69 in margin + 4,50 cm / 1.77 in bar + 77,50 cm / 30.51 in spacing + 4,50 cm / 1.77 in bar + 17 cm / 6.69 in margin
Mounting kit	4 reinforced 5 mm / 0.20 in C-brackets in AISI 304 stainless steel, 8 bolts, nuts and washers in AISI 304




Tools
Maximum load capacity

2 pieces of 10-13 mm / 0.39-0.51 in wrenches
300 kg / 661.39 lb

LIVING SPACE AND INTERNAL DIMENSIONS

Indicative sleeping capacity	3 people
Usable internal depth	234 cm / 92.13 in
Usable internal width	163 cm / 64.17 in
Minimum internal height	70 cm / 27.56 in
Maximum internal height	110 cm / 43.31 in
Mattress	234 × 153 × 5 cm / 92.13 × 60.24 × 1.97 in, single piece



CONSTRUCTION AND MATERIALS

Structure type	Lightweight soft-shell rooftop tent
Opening / closing mechanism	Manual fold-out
Frame / tubing / mechanisms	Internal frame in anodized aluminium tubing Ø 16 mm / 0.63 in, self-supporting arched structure covered with anti-condensation polyester fabric
Perimeter aluminium profiles	Extruded aluminium profiles, Silver anodized finish
Base panels / floor	Two panels with electro-welded aluminium frame and polyurethane foam filling for improved insulation
Main fabric / upper rainfly	210 D Rip-stop Oxford Polyester, 2.000 mm waterproof, black, UPF 50+ and anti-mildew treatment with black PU inner coating
Travel cover / outer cover	PVC 500 g / 600 D, waterproof, UPF 50+ treatment; printed logo
Mattress / soft cover	High density, 50 mm / 1.97 in thickness with removable, washable cover
Zippers	SBS with high-glide plastic pulls
Skylights	PVC with UPF 50+ treatment
Mosquito nets	High-density polyester insect mesh (approx. 28 mesh)
Hardware	Bolts, washers, main brackets and movement hinges in AISI 304 stainless steel; kit with 4 reinforced 5 mm / 0.20 in bent brackets
Shoe storage bags	Standard with weather protection
Closure locking system	4 velcro straps with rings to secure the tent in closed position
Accidental closure safety system	2 manual hooks on the central hinges lock the tent in the open position
Metal tensioning rods	Rods for tensioning the rear rainfly fabric, galvanized spring steel

LADDER

Telescopic ladder operation	Recommended maximum ladder anchor height 185 cm / 72.83 in
Ladder model	1 type C ladder, angled step, silver-coloured aluminium
Ladder weight	4,20 kg / 9.26 lb
Extension	110-190 cm / 43.31-74.80 in
Maximum load capacity	130 kg / 286.60 lb

ACCESSORIES AND EQUIPMENT

Complete tent	1 unit
Mattress	1 single-piece set; 4 kg / 8.82 lb
Anti-condensation mesh	Not included
Thermal cover	Not included
Travel cover / outer cover	1 PVC piece; 3 kg / 6.61 lb
Mounting kit	Bolts, brackets and tools; 1,654 kg / 3.65 lb
Shoe storage bags	2 shoe storage bags, 0,20 kg / 0.44 lb total
LED / USB cable	Not included
Telescopic pole / rods	Not included
Ratchets / pegs / guy lines	Not included
Pockets / organizers	2 internal
Metal tensioning rods	4 galvanized spring steel rods
Telescopic ladder	1 piece; 4,20 kg / 9.26 lb